Technical Data Sheet

6 V 10 Ah LiFePO4 Lithium Battery



Reference | B06010

Technical Specifications

Product Reference: B06010
Technology: Lithium Iron Phosphate
Nominal Voltage: 6.4 V
Minimum Capacity: 9.6 Ah
Energy: 38 Wh
Charging Voltage: 7.3 V
Standard Charging Current: 5 A
Fast Charging Current: 8 A
Continuous Discharge Current: 10 A
Pulse Discharge Current: 30 A (max. 5 min)
Self-Discharge: < 3% per month
Operating Temperature: -20°C to +60°C
Charging Temperature: 0°C to +45°C
Cycle Life: 2,000 at 1C, 100% DOD

Battery Management by BMS

- ✓ Short-circuit protection
- ✓ Overcharge protection
- ✓ Deep-discharge protection (voltage < 5 V)
- ✓ High-temperature protection (> 65°C)
- ✓ Battery cut-off with automatic reconnection
- ✓ Cell balancing

Connection

30 cm wires with Anderson PP30 connector

Weight: 540 g
Dimensions: 85 (L) x 57 (W) x 76 (H) mm


IP50 (no protection against water ingress)

CE RoHS Compliant UN38.3 PASSED Transport Safety Certified

Technical Data Sheet


Different Rate Discharge Curve

Different Rate Discharge Curve @25℃




Different Temperature Discharge Curve

Different Temperature Discharge Curve @0.5C




State of Charge Curve

State of Charge Curve @0.5C 25℃




Charging Characteristics

Charging Characteristics @0.5C 25℃



Cycle Life Curve

Different DOD Discharge Cycle Life Curve @1C



Self Discharge Characteristics Curve

Different Temperature Self Discharge Curve

