Technical Data Sheet

24 V 76 Ah LiFePO4 Lithium Battery



Reference | B24076L

Technical Specifications

Product reference: B24076L
Technology: Lithium Iron Phosphate
Nominal voltage: 25.6 V
Minimum capacity: 76 Ah
Energy: 1,966 Wh
Charging voltage: 29.2 V
Standard charging current: 40 A
Fast charging current: 80 A
Continuous discharge current: 100 A
Pulse discharge current: 150 A (10 s)
Self-discharge: < 3% / month
Operating temperature: -20°C to +60°C
Charging temperature: 0°C to +45°C
Cycle life: 2,000 at 1C, 100% DOD

Battery Management System (BMS)


- Short-circuit protection
- Overcharge protection (350 A +/- 60 A)
- Deep-discharge protection
- Battery cut-off below 18 V
- Overtemperature protection
- Battery cut-off above 65°C
- Automatic reconnection after protection cut-off
- Cell balancing

Connection

M8 screw terminals

Weight: 21.5 kg
Dimensions: 328 (L) × 173 (W) × 212 (H) mm


IP51 (protection against vertically falling water drops)



Technical Data Sheet


Different Rate Discharge Curve

Different Rate Discharge Curve @25℃




Different Temperature Discharge Curve

Different Temperature Discharge Curve @0.5C




State of Charge Curve

State of Charge Curve @0.5C 25℃




Charging Characteristics

Charging Characteristics @0.5C 25℃



Cycle Life Curve

Different DOD Discharge Cycle Life Curve @1C



Self Discharge Characteristics Curve

Different Temperature Self Discharge Curve

